

## 5 t h A V E N U E

The landmark of classic styling and exceptional performance, 5th Avenue stands as a radiant choice for demanding commercial spaces. Its rugged textured loop design provides a refined, understated atmosphere. Constructed of DuPont DSDN® solution dyed nylon, 5th Avenue weathers rush hours and keeps its crisp, tailored appearance.



Cambridge

Cambridge Commercial Carpets

201 Princeton Boulevard

P.O. Box 1110

Adairsville, Georgia 30103

800 451 1250

335 Roxton Street

Acton Vale, Quebec

Canada J0H 1A0

888 467 5075

[www.cambridgecarpet.com](http://www.cambridgecarpet.com)

**Construction:**

Textured Loop Pattern

**Yarn Content:**

DuPont DSDN® Nylon

**Dye Method:**

Solution

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

15 S.P.I. (59.1/10 cm.)

**Pile Height Tufted:**

.250 in. (6.35 mm.) high

.125 in. (3.18 mm.) low

**Yarn Weight Tufted:**

28 oz./yd.<sup>2</sup> (949 g./m.<sup>2</sup>)

**Primary Backing:**

PatternLok™ Woven Primary

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less Than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Pattern Repeat:**

.40" W x .50"L (1.0 cm. x 1.3 cm.)

**Backing Options:**

See iLoc™ Folder For Additional Backing Options