

B I L T M O R E I I

A textured loop, Biltmore II construction offers exceptional performance. Biltmore II comes in 24 rich, dramatic colorways.

Cambridge®

A Beaulieu Commercial Brand
201 Princeton Boulevard
P.O. Box 1110
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

Construction:

Textured Loop

Yarn Content:

Diatron® SD Nylon

Dye Method:

Solution Dyed

Gauge:

1/10 in. (39.4 col./10 cm.)

Stitch Count:

9.3 S.P.I. (36.7 / 10 cm.)

Pile Height:

.187 in. (4.77 mm.) avg

Yarn Weight Tufted:

28 oz./yd² (949 g. /m.²)

Primary Backing:

Polypropylene

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66m.)

Static Control:

Less Than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class I (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Soil Resistance:

Commercial Anti-Soil Protection

Warranties:

10 Year Limited Warranty
10 Year Stain Removal Warranty

Pattern Repeat:

Random Match