

C A P E C O D

Cambridge®

A Beaulieu Commercial Brand

201 Princeton Boulevard

P.O. Box 1110

Adairsville, Georgia 30103

800 451 1250

335 Roxton Street

Acton Vale, Quebec

Canada J0H 1A0

888 467 5075

Construction:

Patterned Cut Pile

Yarn Content:

Continuous Filament 6,6 Nylon

Dye Method:

Applied Pattern

Machine Gauge:

1/10 in. (39.4 col./10 cm.)

Stitch Count:

9.5 S.P.I. (37.7/10 cm.)

Pile Height Tufted:

.297 in. (7.5 mm.)

Yarn Weight Tufted:

36 oz./yd.² (1220 g./m.²)

Primary Backing:

Polypropylene

Secondary Backing:

Action Bac®

Width:

12 feet (3.66 m.)

Static Control:

Less Than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class 1 (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)
Passes CAN S102.2

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty

Pattern Repeat:

18" W x 18" L (45.7 cm. x 45.7 cm.)

Coordinating Styles:

Kennebunkport / Nantucket