

# DAVOS II:

**Style Number**

DS

## Specifications

<b>Construction</b>	Cut/Loop
<b>Yarn Content</b>	100% Ultron® Nylon 6,6 Premium Branded Fiber
<b>Dye Method</b>	Beck
<b>Machine Gauge</b>	1/8 in. (31.5 col./10 cm.)
<b>Stitch Count</b>	14 S.P.I. (55/10 cm.)
<b>Finished Pile Thickness</b>	.156 in. (4.0 mm.)
<b>Average Density</b>	7,345
<b>Yarn Weight Tufted</b>	38 oz./yd.2 (1288 g./m2)
<b>Primary Backing</b>	Polypropylene
<b>Secondary Backing</b>	Woven Polypropylene with Post Consumer Recycled
<b>Width</b>	12 feet (3.66m.)
<b>Pattern Repeat</b>	.50" w x .50" l (1.3 cm. x 1.3" cm.)

## Performance

<b>Static Control</b>	Less Than 3.5 k.v. Step
<b>Flame Resistance</b>	Passes (DOC FF-1-70)
<b>Flooring Radiant Panel</b>	Class 1 (ASTM E-648)
<b>Smoke Density</b>	Less Than 450 (ASTM E-662)
<b>Soil Resistance</b>	Commercial Anti-Soil Protection
<b>CRI Green Label Plus</b>	Certification # GLP3078

## Warranties

<b>Wear</b>	Lifetime Limited Warranty
<b>Static</b>	Lifetime Warranty

## Additional Information

<b>Custom Colors</b>	Contact Sales Representative
<b>Backing Options</b>	See iLoc® Folder
<b>Coordinating Styles</b>	Multiple
<b>Samples</b>	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



# B Ö L Y Ü

201 Princeton Boulevard  
Adairsville, Georgia 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075