

## Combo #02

**Construction:**

Textured Loop Pattern

**Yarn Content:**

Diatron® SD nylon

**Dye Method:**

Solution

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

10.0 S.P.I. (39.4/10 cm.)

**Pile Height Tufted:**

.219 in. (5.57 mm.) high  
.156 in. (3.96 mm.) low

**Yarn Weight Tufted:**

26 oz./yd.<sup>2</sup> (881 g./m.<sup>2</sup>)

**Primary Backing:**

Polypropylene

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Backing Options:**

See iLoc™ Folder For  
Additional Backing Options

## Combo #04

**Construction:**

Textured Loop Pattern

**Yarn Content:**

Diatron® SD nylon

**Dye Method:**

Solution

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

9.0 S.P.I. (35.4/10 cm.)

**Pile Height Tufted:**

.219 in. (5.57 mm.) high  
.125 in. (3.18 mm.) low

**Yarn Weight Tufted:**

26 oz./yd.<sup>2</sup> (881 g./m.<sup>2</sup>)

**Primary Backing:**

PatternLoc™ Woven Primary

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Backing Options:**

See iLoc™ Folder For  
Additional Backing Options

**Pattern Repeat:**

.40" W x .67" L  
(1.0cm. x 1.7cm.)

## Combo #05

**Construction:**

Textured Loop Pattern

**Yarn Content:**

Diatron® SD nylon

**Dye Method:**

Solution

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

6.9 S.P.I. (27.2/10 cm.)

**Pile Height Tufted:**

.218 in. (5.54 mm.) high  
.156 in. (3.96 mm.) low

**Yarn Weight Tufted:**

26 oz./yd.<sup>2</sup> (881 g./m.<sup>2</sup>)

**Primary Backing:**

Polypropylene

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Backing Options:**

See iLoc™ Folder For  
Additional Backing Options

**Pattern Repeat:**

.60" W x 1.6" L  
(1.5cm. x 4.1cm.)

## Combo #06

**Construction:**

Cut Pile

**Yarn Content:**

DuPont XT1® nylon

**Dye Method:**

Piece

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

8.3 S.P.I. (32.8/10 cm.)

**Pile Height Tufted:**

.281 in. (7.14 mm.)

**Yarn Weight Tufted:**

26 oz./yd.<sup>2</sup> (881 g./m.<sup>2</sup>)

**Primary Backing:**

Polypropylene

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Custom Colors:**

Contact Mill Representative



### Combo #01

**Construction:**  
Textured Loop Pattern

**Yarn Content:**  
Diatron® SD nylon/BCF nylon

**Dye Method:**  
Solution/Space Dyed

**Machine Gauge:**  
1/10in. (39.4 col./10 cm.)

**Stitch Count:**  
10.0 S.P.I. (39.4/10 cm.)

**Pile Height Tufted:**  
.187 in. (4.76 mm.) high  
.156 in. (3.96 mm.) low

**Yarn Weight Tufted:**  
26 oz./yd.<sup>2</sup> (881 g./m.<sup>2</sup>)

**Primary Backing:**  
Polypropylene

**Secondary Backing:**  
Woven Polypropylene

**Width:**  
12 feet (3.66 m.)

**Static Control:**  
Less than 3.5 K.V. Step

**Flame Resistance:**  
Passes (DOC FF-1-70)

**Flooring Radiant Panel:**  
Class 1 (ASTM E-648)

**Smoke Density:**  
Less Than 450 (ASTM E-662)

**Soil Resistance:**  
Commercial Anti-Soil Protection

**Wear Warranty:**  
10 Year Limited Warranty

**Backing Options:**  
See iLoc™ Folder For  
Additional Backing Options

**Pattern Repeat:**  
.40" W x .50" L  
(1.0cm. x 1.3cm.)

### Combo #02

**Construction:**  
Textured Loop

**Yarn Content:**  
Diatron® SD nylon

**Dye Method:**  
Solution

**Machine Gauge:**  
1/10in. (39.4 col./10 cm.)

**Stitch Count:**  
10.0 S.P.I. (39.4/10 cm.)

**Pile Height Tufted:**  
.219 in. (5.57 mm.) high  
.156 in. (3.96 mm.) low

**Yarn Weight Tufted:**  
26 oz./yd.<sup>2</sup> (881 g./m.<sup>2</sup>)

**Primary Backing:**  
Polypropylene

**Secondary Backing:**  
Woven Polypropylene

**Width:**  
12 feet (3.66 m.)

**Static Control:**  
Less than 3.5 K.V. Step

**Flame Resistance:**  
Passes (DOC FF-1-70)

**Flooring Radiant Panel:**  
Class 1 (ASTM E-648)

**Smoke Density:**  
Less Than 450 (ASTM E-662)

**Soil Resistance:**  
Commercial Anti-Soil Protection

**Wear Warranty:**  
10 Year Limited Warranty

**Backing Options:**  
See iLoc™ Folder For  
Additional Backing Options

### Combo #07

**Construction:**  
Textured Loop Pattern

**Yarn Content:**  
Diatron® SD nylon

**Dye Method:**  
Solution

**Machine Gauge:**  
1/10in. (39.4 col./10 cm.)

**Stitch Count:**  
9.0 S.P.I. (35.4/10 cm.)

**Pile Height Tufted:**  
.187 in. (4.76 mm.) high  
.094 in. (2.38 mm.) low

**Yarn Weight Tufted:**  
28 oz./yd.<sup>2</sup> (949 g./m.<sup>2</sup>)

**Primary Backing:**  
PatternLoc™ Woven Primary

**Secondary Backing:**  
Woven Polypropylene

**Width:**  
12 feet (3.66 m.)

**Static Control:**  
Less than 3.5 K.V. Step

**Flame Resistance:**  
Passes (DOC FF-1-70)

**Flooring Radiant Panel:**  
Class 1 (ASTM E-648)

**Smoke Density:**  
Less Than 450 (ASTM E-662)

**Soil Resistance:**  
Commercial Anti-Soil Protection

**Wear Warranty:**  
10 Year Limited Warranty

**Backing Options:**  
See iLoc™ Folder For  
Additional Backing Options

**Pattern Repeat:**  
.40" W x .50" L  
(1.0cm. x 1.3cm.)

### Combo #08

**Construction:**  
Cut Pile

**Yarn Content:**  
DuPont XT1® nylon

**Dye Method:**  
Piece

**Machine Gauge:**  
1/10in. (39.4 col./10 cm.)

**Stitch Count:**  
10.0 S.P.I. (39.4/10 cm.)

**Pile Height Tufted:**  
.281 in. (7.14 mm.)

**Yarn Weight Tufted:**  
30 oz./yd.<sup>2</sup> (1017 g./m.<sup>2</sup>)

**Primary Backing:**  
Polypropylene

**Secondary Backing:**  
Woven Polypropylene

**Width:**  
12 feet (3.66 m.)

**Static Control:**  
Less than 3.5 K.V. Step

**Flame Resistance:**  
Passes (DOC FF-1-70)

**Flooring Radiant Panel:**  
Class 1 (ASTM E-648)

**Smoke Density:**  
Less Than 450 (ASTM E-662)

**Soil Resistance:**  
Commercial Anti-Soil Protection

**Wear Warranty:**  
10 Year Limited Warranty

**Custom Colors:**  
Contact Mill Representative



### Combo #09

**Construction:**

Textured Loop Pattern

**Yarn Content:**

DuPont® DSDN® solution dyed nylon

**Dye Method:**

Solution

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

9.0 S.P.I. (35.4/10 cm.)

**Pile Height Tufted:**

.187 in. (4.76 mm.) high  
.094 in. (2.4 mm.) low

**Yarn Weight Tufted:**

26 oz./yd.<sup>2</sup> (881 g./m.<sup>2</sup>)

**Primary Backing:**

Polypropylene

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Backing Options:**

See iLoc™ Folder For Additional Backing Options

**Pattern Repeat:**

.40" W x .60" L  
(1.0cm. x 1.5cm.)

### Combo #10

**Construction:**

Cut Pile

**Yarn Content:**

DuPont XT® nylon

**Dye Method:**

Piece

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

12.0 S.P.I. (47.2/10 cm.)

**Pile Height Tufted:**

.313 in. (7.94 mm.)

**Yarn Weight Tufted:**

36 oz./yd.<sup>2</sup> (1220 g./m.<sup>2</sup>)

**Primary Backing:**

Polypropylene

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Backing Options:**

See iLoc™ Folder For Additional Backing Options

**Custom Colors:**

Contact Mill Representative

### Combo #11

**Construction:**

Textured Loop

**Yarn Content:**

DuPont® DSDN® solution dyed nylon

**Dye Method:**

Solution

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

7.9 S.P.I. (31.0/10 cm.)

**Pile Height Tufted:**

.197 in. (5.0 mm.) high  
.125 in. (3.2 mm.) low

**Yarn Weight Tufted:**

28 oz./yd.<sup>2</sup> (949 g./m.<sup>2</sup>)

**Primary Backing:**

Polypropylene

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Backing Options:**

See iLoc™ Folder For Additional Backing Options

### Combo #12

**Construction:**

Textured Loop Pattern

**Yarn Content:**

DuPont B.C.F. nylon

**Dye Method:**

Solution/Space Dye

**Machine Gauge:**

1/10in. (39.4 col./10 cm.)

**Stitch Count:**

8.0 S.P.I. (31.5/10 cm.)

**Pile Height Tufted:**

.218 in. (5.54 mm.) high  
.187 in. (4.76 mm.) low

**Yarn Weight Tufted:**

26 oz./yd.<sup>2</sup> (881 g./m.<sup>2</sup>)

**Primary Backing:**

Polypropylene

**Secondary Backing:**

Woven Polypropylene

**Width:**

12 feet (3.66 m.)

**Static Control:**

Less than 3.5 K.V. Step

**Flame Resistance:**

Passes (DOC FF-1-70)

**Flooring Radiant Panel:**

Class 1 (ASTM E-648)

**Smoke Density:**

Less Than 450 (ASTM E-662)

**Soil Resistance:**

Commercial Anti-Soil Protection

**Wear Warranty:**

10 Year Limited Warranty

**Backing Options:**

See iLoc™ Folder For Additional Backing Options

**Pattern Repeat:**

.80" W x 1.0" L  
(2.0cm. x 2.5cm.)



Cambridge®  
Cambridge Commercial Carpets

www.cambridgecarpet.com

201 Princeton Boulevard  
P.O. Box 1110  
Adairsville, Georgia 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
888 467 5075