

KINSALE

INSPIRED BY A CHARMING SEASIDE FISHING VILLAGE IN IRELAND, BÖLYÜ® HAS CREATED KINSALE, A SMALL-SCALE GRID DESIGN, USING TECHNICALLY ADVANCED LOOP-OVER-LOOP CONSTRUCTION.

THE BLENDING OF SOLID AND MULTI-COLORED SOLUTION DYED NYLON YARNS PRODUCES THE RICH VISUAL EFFECT. ITS MIXTURE OF BULKY YARNS WITH TIGHTLY TWISTED YARNS ADDS MORE TEXTURE AND ENHANCES THE PERFORMANCE WITH GREATER DENSITY.

KINSALE'S TRANSITIONAL COLOR PALETTE CONSISTS OF STRONG NEUTRALS AND EVOLVING COLOR COMBINATIONS OF WARM AND COOL HUES. WHILE EMPHASIZING NEUTRALS, THE BÖLYÜ® SIGNATURE LINE ALSO OFFERS A WIDE SELECTION OF MID-TONES AND MORE SATURATED COLOR OPTIONS. KINSALE ALSO COORDINATES WITH BANTRY, BEDROCK, AND LIMERICK FROM BÖLYÜ®.

BÖLYÜ®, A BEAULIEU COMMERCIAL BRAND, MANUFACTURES HIGHLY STYLED COMMERCIAL CARPETS MARKETED TO ARCHITECTS AND INTERIOR DESIGNERS FOR CORPORATE, INSTITUTIONAL AND RETAIL ENVIRONMENTS.

FOR SAMPLES, CALL — 800.451.1240.

S
P
E
C
I
F
I
C
A
T
I
O
N
S

CONSTRUCTION:	Tetxured Loop Pattern
YARN CONTENT:	Bölyü® Solution Dyed Nylon
DYE METHOD:	Solution dyed
MACHINE GAUGE:	1/10 in. (39.4 col./10 cm.)
STITCH COUNT:	12 S.P.I. (47.2/10 cm.)
PILE HEIGHT TUFTED:	.219 in. (5.56 mm.) high .125in. (3.18 mm.) low
YARN WEIGHT TUFTED:	30 oz./yd. ² (1017 g./m. ²)
PRIMARY BACKING:	Polypropylene
SECONDARY BACKING:	Precision Plus™
WIDTH:	12 feet (3.66 m.)
STATIC CONTROL:	Less Than 3.5 K.V. Step
FLAME RESISTANCE:	Passes (DOC FF-1-70)
FLOORING RADIANT PANEL:	Class 1 (ASTM E-648)
SMOKE DENSITY:	Less Than 450 (ASTM E-662)
SOIL RESISTANCE:	Commercial Anti-Soil Protection
WEAR WARRANTY:	10 Year Limited Warranty
PATTERN REPEAT:	.40" W x .63" L (1.0 cm. x 1.6 cm.)
COORDINATING STYLES:	Bantry / Bedrock / Limerick