

L O D G E

CONSORT®
Hospitality Carpet

201 Princeton Boulevard
P.O. Box 1110
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

www.consorthospitality.com

Construction:

Cut / Loop

Yarn Content:

Diatron® SD Nylon

Dye Method:

Solution

Gauge:

1 / 8 in. (31.5 col. / 10 cm.)

Stitch Count:

13.6 S.P.I. (53.8 / 10 cm.)

Pile Height:

.313 in. (7.94 mm.) high

.218 in. (5.54 mm.) low

Yarn Weight Tufted:

30 oz. / yd² (1017 g. / m.²)

Primary Backing:

Polypropylene

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66 m.)

Static Propensity:

Less than 3.5 KV Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class I (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty

Pattern Repeat:

.50" W x .88" L (1.3 cm. x 2.2 cm.)