

OXFORD III

A multi-colored textured level loop, Oxford III
comes in 19 rich colorways.

Cambridge®

A Beaulieu Commercial Brand
201 Princeton Boulevard
P.O. Box 1110
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

Construction:

Textured Loop

Yarn Content:

Diatron® SD Nylon

Dye Method:

Solution dyed

Machine Gauge:

1/8 in. (31.5 col./10 cm.)

Stitch Count:

10 S.P.I. (39.4/10 cm.)

Pile Height Tufted:

.187 in. (4.76 mm.) high

.156 in. (3.96 mm.) low

Yarn Weight Tufted:

28 oz./yd.² (949 g./m.²)

Primary Backing:

Polypropylene

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66 m.)

Static Control:

Less Than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class 1 (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty

Pattern Repeat:

N/A

Coordinating Styles:

Awards / The Loop / Wallingford / Wesley