

PIONEER

A charter member of the American Pioneer Collection, this ingenious interloop design retains its handsome appearance under heavy commercial use. Its distinctive character is attributed to a combination of dimensional loop construction, color and pattern.



Cambridge®

Cambridge Commercial Carpets

201 Princeton Boulevard

P.O. Box 1110

Adairsville, Georgia 30103

800 451 1250

335 Roxton Street

Acton Vale, Quebec

Canada J0H 1A0

888 467 5075

www.cambridgecarpet.com

Construction:

Interloop Pattern

Yarn Content:

Diatron® SD/BCF nylon

Dye Method:

Solution/Space Dye

Machine Gauge:

1/12in. (47.2 col./10 cm.)

Stitch Count:

10 S.P.I. (39.4/10 cm.)

Pile Height Tufted:

.250 in. (6.35 mm.) high

.094 in. (2.38 mm.) low

Yarn Weight Tufted:

28 oz./yd.² (949 g./m.²)

Primary Backing:

PatternLok™ Woven Primary

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66 m.)

Static Control:

Less than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class 1 (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty

Pattern Repeat:

24" W x 25" L [61 cm. x 63.5 cm.]

Backing Options:

See iLoc™ Folder For Additional Backing Options

Coordinating Styles:

Aviator

Founder

Inventor