

P L I Q U E - A - J O U R

Cambridge®

201 Princeton Boulevard

P.O. Box 1110

Adairsville, Georgia 30103

800 451 1250

335 Roxton Street

Acton Vale, Quebec

Canada J0H 1A0

888 467 5075

Construction:

Textured Loop Pattern

Yarn Content:

DuPont DSDN® Solution Dyed Nylon

Dye Method:

Solution

Machine Gauge:

1/10 in. (39.4 col./10 cm.)

Stitch Count:

8.5 S.P.I. (33.5/10 cm.)

Pile Height Tufted:

.177 in. (4.5 mm.) high

.138 in. (3.5 mm.) low

Yarn Weight Tufted:

28 oz./yd.² (949 g./m.²)

Primary Backing:

Polypropylene

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66 m.)

Static Control:

Less Than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class 1 (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Flame Spread:

Passes (CAN S102.2)

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty

Pattern Repeat:

1.2" W x .80" L (3.0 cm. x 2.0 cm.)

Coordinating Styles:

Gamma 28 / Limoges