

## SPECIFICATIONS

<b>Construction</b>	Textured Loop Pattern
<b>Yarn Content</b>	Cambridge Approved / BCF Nylon
<b>Dye Method</b>	Solution / Space
<b>Machine Gauge</b>	1/10 in (39.4 in./10 cm.)
<b>Stitch Count</b>	12.6 S.P.I (49.6/ 10 cm.)
<b>Finished Pile Thickness</b>	.155 in. (3.94 mm)
<b>Average Density</b>	6,039
<b>Yarn Weight Tufted</b>	26 oz. /yd. <sup>2</sup> (881 g./m. <sup>2</sup> )
<b>Primary Backing</b>	Masterline <sup>®</sup> Woven Primary
<b>Secondary Backing</b>	Woven Polypropylene with Post Consumer recycled Content
<b>Width</b>	12 feet (3.66 m.)
<b>Pattern Repeat</b>	.60" w x .79" l (1.5 cm. x 2.0 cm.)
<b>Total Recycled Content</b>	2.58%

## PERFORMANCE

<b>Static Control</b>	Less Than 3.5 K.V. Step
<b>Flame Resistance</b>	Passes (DOC FF-1-70)
<b>Flooring Radiant Panel</b>	Class 1 (ASTM E-648)
<b>Smoke Density</b>	Less than 450 (ASTM E-662)
<b>Soil Resistance</b>	Commercial Anti-Soil Protection
<b>CRI Green Label Plus</b>	Certification # GLP7078

## WARRANTIES

<b>Wear</b>	10 Year Limited Warranty
-------------	--------------------------

## ADDITIONAL INFORMATION

<b>Custom Colors</b>	Contact Sales Representative
<b>Backing Options</b>	See iLoc <sup>®</sup> backings at <a href="http://www.ccambrdigecarpet.com">www.ccambrdigecarpet.com</a>
<b>Coordinating Styles</b>	Multiple
<b>Samples</b>	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Carpet Design<sup>®</sup> 2003 Beaulieu Group, LLC.

## PORTFOLIO

style # 6PTF

# Cambridge<sup>®</sup>

201 Princeton Boulevard  
P.O. Box 1110  
Adairsville, GA 30103  
800 451 1250

335 Roxton Street  
Acton Vale, Quebec  
Canada JOH 1A0  
888 467 5075

[www.cambridgecarpet.com](http://www.cambridgecarpet.com)

A Beaulieu Commercial Brand