

R O U T E 6 6 , E X I T 2 6

R O U T E 6 6 , E X I T 3 0

R O U T E 6 6 , E X I T 3 6



Cambridge®

Cambridge Commercial Carpets

201 Princeton Boulevard

P.O. Box 1110

Adairsville, Georgia 30103

800 451 1250

335 Roxton Street

Acton Vale, Quebec

Canada J0H 1A0

888 467 5075

www.cambridgecarpet.com

Construction:

Cut Pile

Yarn Content:

DuPont XTI®

Dye Method:

Piece

Machine Gauge:

1 / 10in. (39.4 col. / 10 cm.)

Stitch Count:

8.3 S.P.I. (32.8 / 10 cm.)

10.0 S.P.I. (39.4 / 10 cm.)

12.0 S.P.I. (47.2 / 10 cm.)

Pile Height Tufted:

.281 in. (7.14 mm.) 26

.281 in. (7.14 mm.) 30

.313 in. (7.94 mm.) 36

Yarn Weight Tufted:

26 oz./yd.² (881 g./m.²)

30 oz./yd.² (1017 g./m.²)

36 oz./yd.² (1022 g./m.²)

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66 m.)

Static Control:

Less than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class 1 (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty