

S O L A R I S

CONSORT®
Hospitality Carpet

201 Princeton Boulevard
P.O. Box 1110
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

www.consorthospitality.com

Construction:

Cut Pile

Yarn Content:

Continuous Filament 6,6 Nylon

Dye Method:

Applied Pattern

Gauge:

1/10 in. (39.4 col./10 cm.)

Stitch Count:

9.5 S.P.I. (37.7/10 cm.)

Pile Height:

.297 in. (7.5 mm.)

Yarn Weight Tufted:

36 oz./yd² (1220 g. /m.²)

Primary Backing:

Woven Polypropylene

Secondary Backing:

Action Bac

Width:

12 feet (3.66 m.)

Static Propensity:

Less than 3.5 KV Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class I (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)
Passes CAN S102.2

Soil Resistance:

Commercial Anti-Soil Protection

Warranties:

10 Year Limited Warranty

Pattern Repeat:

36" W x 36" L (91.4 cm. x 91.4 cm.)