

S U M M I T

Cambridge®

A Beaulieu Commercial Brand

201 Princeton Boulevard

P.O. Box 1110

Adairsville, Georgia 30103

800 451 1250

335 Roxton Street

Acton Vale, Quebec

Canada J0H 1A0

888 467 5075

Construction:

Textured Loop Pattern

Yarn Content:

Diatron® SDN / BCF Nylon

Dye Method:

Solution / Space dyed

Machine Gauge:

1/10 in. (39.4 col./10 cm.)

Stitch Count:

13 S.P.I. (51.2/10 cm.)

Pile Height Tufted:

.218 in. (5.54 mm.) high

.094 in. (2.38 mm.) low

Yarn Weight Tufted:

28 oz./yd.² (949 g./m.²)

Primary Backing:

Polypropylene

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66 m.)

Static Control:

Less Than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class 1 (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty

Pattern Repeat:

.40" W x .50" L (1.0 cm. x 1.3 cm.)

Coordinating Styles:

Expedition / Foxcroft / Laurel Springs / Turnberry