

VECTOR

Energetic color combinations are offered in the textural woven look of Vector. Fourteen colorways coordinate with Tangent and Gamma 28 for versatility in a single commercial application. For optimum performance Vector is constructed of 100% DuPont BCF Nylon.

Cambridge®

201 Princeton Boulevard
P.O. Box 1110
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

Construction:

Textured Loop Pattern

Yarn Content:

DuPont BCF Nylon

Dye Method:

Solution / Space

Machine Gauge:

1/10 in. (39.4 col./10 cm.)

Stitch Count:

11.3 S.P.I. (44.6/10 cm.)

Pile Height Tufted:

.250 in. (6.4 mm.) high

.125 in. (3.2 mm.) low

Yarn Weight Tufted:

28 oz./yd.² (949 g./m.²)

Primary Backing:

Polypropylene

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66 m.)

Static Control:

Less Than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class 1 (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty

Pattern Repeat:

.40" W x .63" L (1.0 cm. x 1.6 cm.)

Coordinating Styles:

Gamma 28 / Tangent