

W Y N F O R D I I I

Cambridge®

A Beaulieu Commercial Brand

201 Princeton Boulevard

P.O. Box 1110

Adairsville, Georgia 30103

800 451 1250

335 Roxton Street

Acton Vale, Quebec

Canada J0H 1A0

888 467 5075

Construction:

Textured Loop

Yarn Content:

Diatron® SD Nylon

Dye Method:

Solution dyed

Machine Gauge:

1/10 in. (39.4 col./10 cm.)

Stitch Count:

10 S.P.I. (39.4/10 cm.)

Pile Height Tufted:

.219 in. (5.57 mm.) high

.156 in. (3.96 mm.) low

Yarn Weight Tufted:

26 oz./yd.² (881 g./m.²)

Primary Backing:

Polypropylene

Secondary Backing:

Woven Polypropylene

Width:

12 feet (3.66 m.)

Static Control:

Less Than 3.5 K.V. Step

Flame Resistance:

Passes (DOC FF-1-70)

Flooring Radiant Panel:

Class 1 (ASTM E-648)

Smoke Density:

Less Than 450 (ASTM E-662)

Soil Resistance:

Commercial Anti-Soil Protection

Wear Warranty:

10 Year Limited Warranty

Pattern Repeat:

N/A